Polycom[®] SoundPoint[®] IP 450 Mid-Range SIP desktop phone with Polycom HD Voice[™]



Three-line desktop phone featuring Polycom HD Voice and productivity enhancing applications through a high-resolution, graphical backlit display.

The SoundPoint IP 450 desktop phone is designed to bring advanced telephony features and applications to cubicle/office workers handling a moderate volume of calls. With its high-resolution, graphical backlit display supporting multiple languages and Asian characters, applications enabled XML Microbrowser, and Polycom HD Voice, the SoundPoint IP 450 sets new standards for the mid-range SIP desktop phone.

Unsurpassed Voice Quality and Clarity

The SoundPoint IP 450 features Polycom HD Voice, bringing life-like richness and clarity to every call. Polycom HD Voice incorporates wideband audio for over twice the voice clarity, Polycom's patented Acoustic Clarity Technology for crystal-clear, noise and echo-free sound, plus best-in-class system design for high-fidelity voice reproduction.

Easy-to-Use Features and Applications

An enterprise-grade phone, the SoundPoint IP 450 delivers an easy-tonavigate menu and a combination of 17 dedicated hard keys and four content sensitive soft keys on a backlit, multi-level grayscale 171 x 73 pixel LCD display. Hosting a built-in XML Microbrowser, the SoundPoint IP 450 offers an easy- to-access graphical interface to run productivity-enhancing third-party applications using Polycom's flexible and open XML API.

Make Great Things Happen with Polycom SoundPoint IP 450

In today's Internet driven world, the ability to conduct real time communication and collaboration has become critical to an organizations survival. As the market leader in voice, video, data and Web solutions, our award-winning IP telephony and conference technology makes it easy for people to interact and maximize productivity over any network, in just about any environment, anywhere around the globe. That's why more organizations worldwide use and prefer Polycom IP telephony and application solutions. Because when people work together, great things happen. See how you, too, can achieve great things with the Polycom SoundPoint IP 450 desktop phone.

About Polycom

Polycom, Inc. (Nasdaq: PLCM) is the global leader in telepresence, video, and voice solutions and a visionary in communications that empower people to connect and collaborate everywhere. Please visit www.polycom.com for more information.

Find out more

Learn what Polycom VoIP Desktop Phones can do for your organization. Visit us at polycom.com or contact your Polycom representative.

Benefits

Polycom HD Voice – Unparalleled voice clarity to make your calls more efficient and productive.

High-Quality Display – High-resolution graphical 171 x 73 pixel grayscale LCD with adjustable backlighting, applications and Asian character support.

Applications Enabled – Built-in XML Microbrowser to run Polycom Productivity Suite and open API for productivityenhancing third-party applications.

Broad and Robust Interoperability – Certified to interoperate with a broad array of SIP call control platforms to enable open choices and innovations while simplifying provisioning, management, and support.





Lines (Directory Numbers)

• Up to 3 lines with up to 2 concurrent calls per line

Display

- 171 x 73 pixel backlit grayscale graphical LCD
- LED backlight with custom intensity control

Feature Keys

- 4 context-sensitive "soft" keys
- 17 dedicated "hard" keys - 3 line keys with bi-color (red/green) LED
- 3 feature keys
- 5 display/menu navigation keys
- 2 volume control keys
- Mute, headset and hands-free speakerphone
- keys - Dedicated hold key

Headset and Hearing Aid Compatibility

- Dedicated RJ-9 headset port
- Amplified headsets are recommended
 Compliant with ADA Section 508
- Recommendations: Subpart B 1194.23 (all)

 Hearing Aid Compatible (HAC) handset for
- magnetic coupling to approved HAC hearing aids
 Compatible with commercially-available TTY adapter equipment

Audio Features

- Polycom HD Voice technology delivers life-like voice quality for each audio path - the handset, the hands-free speakerphone, and the optional headset
- Full-duplex hands-free speakerphone
 Type 1 compliant with IEEE 1329 full duplex standards
- Frequency response 150Hz 7kHz for handset, optional headset¹ and hands-free speakerphone modes
- Codecs: G.722 (wideband), G.711 µ/A, and G.729A (Annex B)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation/DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Acoustic echo cancellation
- Background noise suppression

Call Handling Features²

- Shared call/bridged line appearance
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Busy Lamp Field (BLF)
- Distinctive incoming call treatment/call waitingCall timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial, redial
- Call waiting

www.polvcom.com

Remote missed call notification

Polycom Worldwide Headquarters 4750 Willow Road, Pleasanton, CA 94588

1.800.POLYCOM or +1.925.924.6000

- Intercom
- Automatic off-hook call placement

Do not disturb function

Other Features

- Integration with Microsoft LCS 2005 for telephone and presence³
 Compatibility with Microsoft Office Communicator
- and Windows® Messenger 5.1 Clients
- Enabled for Polycom Productivity Suite
- Local feature-rich GUITime and date display
- User-configurable contact directory and call history (missed, placed, and received)
- Customizable call progress tones
- Wave file support for call progress tones
- Unicode UTF-8 character support. Multilingual user interface encompassing Chinese, Danish, Dutch, English (Canada/US/UK), French, German, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Slovenian, Spanish, Swedish

Protocol Support

- IETF SIP (RFC 3261 and companion RFCs)
- Network and Provisioning
- Two-port Ethernet Switch
- 10/100Base-TX across LAN and PC ports
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS4 server-based central
- provisioning for mass deploymentsProvisioning and call server redundancy supported
- Provisioning and call server redundancy supported
 Web portal for individual unit configuration
- QoS Support IEEE 802.1p/Q tagging (VLAN),
- Layer 3 TOS, and DSCP
- Network Address Translation (NAT) support –
 static
- RTCP support (RFC 1889)
- Event logging
- Local digit map
- Hardware diagnostics
- Status and statistics

Security²

- Transport Layer Security (TLS)³
- Encrypted configuration files³
- Digest authentication
- Password login
- Support for URL syntax with password for boot server⁴
- HTTPS secure provisioning⁴
- Support for signed software executables⁴

Power

- Built-in, auto-sensing IEEE 802.3af Power over Ethernet (Class 2)
- External Universal AC adapter (24VDC/12W)⁵

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- AS/NZS CISPR 22 Class B
- VCCI Class BEN55024

or by any means, for any purpose other than the recipient's personal use, without the express written permission of Polycom.

EN61000-3-2; EN61000-3-3

© 2010 Polycom, Inc. All rights reserved. POLYCOM[®], the Polycom "Triangles" logo and the names and marks associated with Polycom's products are trademarks and/or service marks of Polycom, Inc. and are registered and/or common law marks in the United States and various other countries. All other trademarks are property of their respective owners. No portion hereof may be reproduced or transmitted in any form

- NZ Telepermit
- ROHS compliantGOST-R
- Safat

Safety UL 60950-1

- OE 00950
 CE Mark
- CAN/CSA-C22.2 No. 60950-1-03

-40 to +70°C (-40 to +160°F)

SoundPoint IP 450 Comes With:

SoundPoint IP 450 console

Handset with handset cord

Network (LAN) cable

Product registration card

Part Numbers/UPC Codes

Singapore and Malaysia

Box Dimensions/Weight

Master Carton Quantity

Country of Origin

Unit weight - 2.4 lbs (1.1 kg)

specific cord kit)5

Ouick Start Guide

 $(W \times H \times D \times T)$

for worldwide

 $(L \times W \times H)$

Five

Warranty

Thailand

One year

headset.

features.

2

5

Temperature: 0 to 40°C (+32 to 104°F)

Relative Humidity: 5% to 95%, noncondensing

Universal Power Adapter (including country

8.5 x 6 x 6.5 in x 2.5 in (21.5 x 15 x 16.5 x 6.5 cm)

2200-12450-001/610807687887 for NA. TWN

2200-12450-002/610807690214 for Japan

2200-12450-012/610807690221 for AU, NZ

2200-12450-016/610807691396 for Korea

2200-12450-022/610807691396 for China

2200-12450-122/610807690245 for ROE

12.5 x 13.25 x 3.5 in (31.75 x 33.5 x 9 cm)

4.4 lbs (2.0 kg) - includes all packaging material

1. To enjoy all the benefits of Polycom HD Voice when using

the phone in the headset mode, you must use a wideband

Most software-enabled features and capabilities must be

Softswitch vendor or service provider for a list of supported

supported by the server, Please contact your IP PBX/

Universal power adapter not included in the PoE version

POLYCOM[®]

1284 0210

3. Requires SIP version 3.1.0 Rev C or higher.

(P/N: 2200-12450-025)

Requires BootROM version 4.1.2 or higher.

2200-12450-025/610807687894 PoE version

2200-12450-015/610807690238 for UK, HK,

EN 60950-1 IEC 60950-1

AS/NZS 60950-1

Operating Conditions

Storage Temperature

Base stand

Size